

ES2000

Addressable wall mount audible/visual-audible alarm indicator

Wall mount addressable audible/visual-audible alarm indicator, IP65 protection rated.

Volume, flash intensity and sound sequences can be selected via the control panel (and diversified in accordance with the situation) from the 14 tones and 16 voice messages available in 8 different languages on-board the device (only for versions with the voice function).*

For models with the voice function, it is also possible to customize tones/voice messages by means of the EITK2000.

The device is powered via the loop but is equipped with terminals for an optional separate power input.



Tone		14 + 16 voice messages		
Sound Output @ 1m		MAX 101 dB	Consumption ES20x0 Versions	From 10 to 40mA depending on the selected tone
Visual Coverage (EN54-23) ES20x0 Versions	High Power	W-3,5-10	Consumption ES20x1 Versions LOW POWER	From 1.4 to 20 mA
	Low Power	W-2,8-7	Operating Temperature	-20 - +70°C
Visual Coverage (EN54-23) ES20x1 Versions LOW POWER	High Power	W-3.5-7 O-3.5-8-7	Weight	150 g
	Low Power	W-3-6.5 O-3-8-6.5	Dimensions	120x120x60 mm
IP Protection Grade		IP65		

Order codes:

ES2010RE – Audible alarm indicator in Red casing

ES2011RE – Audible alarm indicator in Red casing low power

ES2010WE – Audible alarm indicator in White casing

ES2011WE - Audible alarm indicator in White casing low power

ES2020RE – Visual-audible alarm indicator in Red casing

ES2021RE – Visual-audible alarm indicator in Red casing low power

ES2020WE – Visual-audible alarm indicator in White casing

ES2021WE – Visual-audible alarm indicator in White casing low power

ES2030RE – Audible alarm indicator with voice alert In Red casing

ES2030WE – Audible alarm indicator with voice alert in White casing

ES2050RE – Visual-audible alarm indicator with voice alert in Red casing

ES2050WE – Visual-audible alarm indicator with voice alert in White casing